SHC — SOLAR HEATING & COOLING PROGRAMME — INTERNATIONAL ENERGY AGENCY

SHC TASK 66 — Solar Energy Buildings

Task 66: Solar Energy Buildings

Integrated solar energy supply concepts for climate-neutral buildings and communities for the "City of the Future"

Subtask A:
Boundary Conditions, KPIs, Definitions and Dissemination
First Results

**Prof. Frank Späte, OTH Amberg-Weiden, Germany**

Deliverables

D1: List of KPIs (Key Performance Indicators) and Criteria

D2: Definition of Reference Buildings / Cases

D3: Industry Workshops

D4: Solar Energy Building promotion guidelines for investors, building owners and politicians

Energy Flow Diagram

Example: total solar fraction

Designation	Definition / calculation for the case shown in column 'Diagram' (example)	Diagram
total solar fraction [%] = LCF – Load Cover Factor	$$f_{sol} = \frac{E_{PV,tot} - E_{PV,grid} + Q_{ST,tot} - Q_{ST,grid}}{E_{PV,tot} - E_{PV,grid} + E_{grid} + Q_{ST,tot} - Q_{ST,grid} + Q_{DH} + Q_h - Q_{h,el}}$$ Fraction of self-generated and self-used PV electricity and solarthermal useful heat referred to the total energy used for household and technical purposes in the form of heat and electricity. Energy supplied by solar part (PV or ST) of a system divided by the total system load (electrical and thermal).	

A first Draft of the „KPI-list" is now available

Contact us, join us, share your ideas with us!

www.iea-shc.org

Task 66: Solar Energy Buildings

Subtask A: Boundary Conditions, KPIs, Definitions and Dissemination

Frank Späte, OTH-AW, Germany
Email: frank.spaete@oth-aw.de